

LED LIGHTS - TECHNICAL SPECIFICATIONS

Type	Product Code	Power	Lumen	Equal Wattage	Beam Angle	Base	RA	PF	Voltage	Product Size	Body Material
MR16	55.6261	3W	250lm	25W	120°	GU5.3	>70	>0.5	175-265V	ø50*50mm	Plastic
		5W	400lm	40W	120°	GU5.3	>70	>0.5	175-265V	ø50*50mm	PC +Aluminium
		7W	520lm	50W	120°	GU5.3	>70	>0.5	175-265V	ø50*50mm	PC +Aluminium
GU10	55.6262	3W	250lm	25W	120°	GU10	>70	>0.5	175-265V	ø50*56mm	Plastic
		5W	400lm	40W	120°	GU10	>70	>0.5	175-265V	ø50*56mm	PC +Aluminium
		7W	520lm	50W	120°	GU10	>70	>0.5	175-265V	ø50*56mm	PC +Aluminium
MR16	55.6241	3W	250lm	25W	38°	GU5.3	>70	>0.5	175-265V	ø50*50mm	PC +Aluminium
		5W	400lm	40W	38°	GU5.3	>70	>0.5	175-265V	ø50*50mm	PC +Aluminium
		7W	520lm	50W	38°	GU5.3	>70	>0.5	175-265V	ø50*50mm	PC +Aluminium
GU10	55.6243	3W	250lm	25W	38°	GU10	>70	>0.5	175-265V	ø50*56mm	PC +Aluminium
		5W	400lm	40W	38°	GU10	>70	>0.5	175-265V	ø50*56mm	PC +Aluminium
		7W	520lm	50W	38°	GU10	>70	>0.5	175-265V	ø50*56mm	PC +Aluminium
C37	55.621	3W	250lm	25W	220°	E14/E27	>70	>0.5	175-265V	ø37*100mm	Plastic
		5W	400lm	40W	220°	E14/E27	>70	>0.5	175-265V	ø37*100mm	PC +Aluminium
		7W	520lm	50W	220°	E14/E27	>70	>0.5	175-265V	ø37*100mm	PC +Aluminium
F37	55.6212	3W	250lm	25W	220°	E14/E27	>70	>0.5	175-265V	ø37*125mm	Plastic
		5W	400lm	40W	220°	E14/E27	>70	>0.5	175-265V	ø37*125mm	PC +Aluminium
		7W	560lm	50W	220°	E14/E27	>70	>0.5	175-265V	ø37*125mm	PC +Aluminium
G45	55.6214	3W	250lm	25W	220°	E14/E27	>70	>0.5	175-265V	ø45*83mm	Plastic
		5W	400lm	40W	220°	E14/E27	>70	>0.5	175-265V	ø45*83mm	PC +Aluminium
		7W	560lm	50W	220°	E14/E27	>70	>0.5	175-265V	ø45*83mm	PC +Aluminium
A60	55.8337A	5W	400lm	40W	270°	E27	>70	>0.5	175-265V	ø60*110mm	PC +Aluminium
		7W	560lm	50W	270°	E27	>70	>0.5	175-265V	ø60*110mm	PC +Aluminium
A60	55.8337B	10W	800lm	60W	270°	E27	>70	>0.5	175-265V	ø60*110mm	PC +Aluminium
		12W	1000lm	75W	270°	E27	>70	>0.5	175-265V	ø60*110mm	PC +Aluminium
A65	55.6227	15W	1300lm	90W	270°	E27	>70	>0.5	175-265V	ø65*122mm	PC +Aluminium
A70	55.6228	16W	1440lm	100W	270°	E27	>70	>0.5	175-265V	ø70*128mm	PC +Aluminium
G80	55.6004	9W	800lm	60W	220°	E27	>70	>0.5	175-265V	ø80*122mm	PC +Aluminium
G95	55.6005	15W	1050lm	75W	220°	E27	>70	>0.5	175-265V	ø95*140mm	PC +Aluminium
G125	55.6006	18W	1500lm	100W	220°	E27	>70	>0.5	175-265V	ø125*172mm	PC +Aluminium
UFO	55.5012	15W	1200lm	90W	220°	E27	>70	>0.5	175-265V	ø150*80mm	PC +Aluminium
		25W	2000lm	150W	220°	E27	>70	>0.5	175-265V	ø200*80mm	PC +Aluminium

T80/ T100/ T120/T140	55.5006	35W	2800lm	200W	220°	E27	>70	>0.5	175-265V	ø250*80mm	PC +Aluminium
		20W	1600lm	100W	220°	E27	>70	>0.5	175-265V	ø80*142mm	PC +Aluminium
		25W	2000lm	150W	220°	E27	>70	>0.5	175-265V	ø100*172mm	PC +Aluminium
		35W	2800lm	200W	220°	E27	>70	>0.5	175-265V	ø115*202mm	PC +Aluminium
		45W	3600lm	250W	220°	E27	>70	>0.5	175-265V	ø135*227mm	PC +Aluminium
T80/T100/T1 20/T140/T15 0	55.5007	25W	2200lm	150W	220°	E27	>70	>0.5	175-265V	ø80*150mm	Aluminium
		35W	3100lm	200W	220°	E27	>70	>0.5	175-265V	ø100*170mm	Aluminium
		50W	4500lm	300W	220°	E27	>70	>0.5	175-265V	ø120*208mm	Aluminium
		85W	7600lm	400W	220°	E27	>70	>0.5	175-265V	ø138*243mm	Aluminium
		100W	9000lm	500W	220°	E27	>70	>0.5	175-265V	ø150*252mm	Aluminium
T8 GLASS TUBE	55.8103G	9W	900lm		300°	G13	>70	>0.5	175-265V	ø28*588mm	Glass
		18W	1800lm		300°	G13	>70	>0.5	175-265V	ø28*1198mm	Glass
		22W	2200lm		300°	G13	>70	>0.5	175-265V	ø28*1498mm	Glass
T8 NANO TUBE	55.8103P	9W	900lm		300°	G13	>70	>0.5	175-265V	ø28*588mm	Nano
		18W	1800lm		300°	G13	>70	>0.5	175-265V	ø28*1198mm	Nano
		22W	2200lm		300°	G13	>70	>0.5	175-265V	ø28*1498mm	Nano

LED FIXTURES AND FITTINGS - TECHNICAL SPECIFICATIONS

Type	Product Code	Power	Lumen	RA	PF	Voltage	Product Size	Body Material
Recessed	12.2201	3W	165lm	>70	>0.5	175-265V	Ø90*25mm	Aluminum
		6W	330lm	>70	>0.5	175-265V	Ø120*25mm	Aluminum
		9W	495lm	>70	>0.5	175-265V	Ø150*25mm	Aluminum
		12W	660lm	>70	>0.5	175-265V	Ø170*25mm	Aluminum
		15W	900lm	>70	>0.5	175-265V	Ø200*25mm	Aluminum
		18W	1080lm	>70	>0.5	175-265V	Ø220*25mm	Aluminum
		24W	1440lm	>70	>0.5	175-265V	Ø300*25mm	Aluminum
Recessed	12.2211	3W	165lm	>70	>0.5	175-265V	90*90*25mm	Aluminum
		6W	330lm	>70	>0.5	175-265V	120*120*25mm	Aluminum
		9W	495lm	>70	>0.5	175-265V	150*150*25mm	Aluminum
		12W	660lm	>70	>0.5	175-265V	170*170*25mm	Aluminum
		15W	900lm	>70	>0.5	175-265V	200*200*25mm	Aluminum
		18W	1080lm	>70	>0.5	175-265V	220*220*25mm	Aluminum
		24W	1440lm	>70	>0.5	175-265V	300*300*25mm	Aluminum
Surface	15.2123	6W	330lm	>70	>0.5	175-265V	Ø120*32mm	Aluminum
		12W	660lm	>70	>0.5	175-265V	Ø170*32mm	Aluminum
		18W	1080lm	>70	>0.5	175-265V	Ø225*32mm	Aluminum
		24W	1440lm	>70	>0.5	175-265V	Ø300*32mm	Aluminum
Surface	15.2123	6W	330lm	>70	>0.5	175-265V	120*120*32mm	Aluminum
		12W	660lm	>70	>0.5	175-265V	170*170*32mm	Aluminum
		18W	1080lm	>70	>0.5	175-265V	225*225*32mm	Aluminum
		24W	1440lm	>70	>0.5	175-265V	300*300*32mm	Aluminum
Batten	15.3031	18W	1260lm	>70	>0.5	175-265V	600*75*23m	Plastic
		36W	2520lm	>70	>0.5	175-265V	1200*75*23m	Plastic
	15.3032	18W	1260lm	>70	>0.5	175-265V	600*75*23m	Aluminum
		36W	2520lm	>70	>0.5	175-265V	1200*75*23m	Aluminum
	15.7004	20W	2000lm	>70	>0.5	175-265V	620*100*60m	Iron sheet
		40W	4000lm	>70	>0.5	175-265V	1230*100*60	Iron sheet
IP65 weatherproof light	15.3221	18W	1620lm	>70	>0.5	175-265V	605*80*75m	ABS/PC
		36W	3240lm	>70	>0.5	175-265V	1205*80*75m	ABS/PC
		50W	4500lm	>70	>0.5	175-265V	1505*80*75m	ABS/PC
Mirror Light	12.3051C	5W	400lm	>70	>0.5	175-265V	348*66*28.5m	Plastic
		10W	800lm	>70	>0.5	175-265V	578*66*28.5m	Plastic
		15W	1200lm	>70	>0.5	175-265V	900*66*28.5m	Plastic
	12.3051B	5W	400lm	>70	>0.5	175-265V	351*78*35m	Aluminum
		10W	800lm	>70	>0.5	175-265V	579*78*35m	Aluminum
		15W	1200lm	>70	>0.5	175-265V	911*78*35m	Aluminum
	15.6181	7W	500lm	>70	>0.5	175-265V	275*38*55m	Aluminum
		14W	1000lm	>70	>0.5	175-265V	536*38*55m	Aluminum

	15.6183	7W	500lm	>70	>0.5	175-265V	281*38*55m	Aluminum
		14W	1000lm	>70	>0.5	175-265V	542*38*55m	Aluminum
	15.618	7W	500lm	>70	>0.5	175-265V	281*58*47m	Aluminum
		14W	1000lm	>70	>0.5	175-265V	542*58*47m	Aluminum
T5 Fitting	15.3041A	4W	320lm	>70	>0.5	175-265V	300*20*34m	Plastic
		8W	640lm	>70	>0.5	175-265V	600*20*34m	Plastic
		10W	800lm	>70	>0.5	175-265V	900*20*34m	Plastic
		14W	1120lm	>70	>0.5	175-265V	1200*20*34m	Plastic
T8 Fitting	15.6052	9W	810lm	>70	>0.5	175-265V	600*32*36m	Plastic
		18W	1620lm	>70	>0.5	175-265V	1200*32*36m	Plastic
Louver Fitting	15.7201	20W	1500lm	>70	>0.5	175-265V	295*595*60m	Steel sheet+PP
		38W	3200lm	>70	>0.5	175-265V	295*1195*60	
		50W	4400lm	>70	>0.5	175-265V	295*1495*60	
		38W	3400lm	>70	>0.5	175-265V	595*595*60m	
		78W	7800lm	>70	>0.5	175-265V	595*1195*60	
		100W	9500lm	>70	>0.5	175-265V	595*1495*60	